


# COL – L60

## Vapor Phase, Coal Base Carbon

COL-L 60 is a highly active Granular Activated Carbon (GAC) manufactured from selected grades of Bituminous Coal and designed for use in a wide variety of air purification and vapor phase applications. Available in industry standard 4x6, 4x8 and 4x10 mesh sizes, these high quality carbons provide extraordinary surface area, fine pore structure, high density and superior hardness.

### TYPICAL PHYSICAL PROPERTIES / SPECIFICATIONS

Total Surface Area (BET), m <sup>2</sup> /gm	1050-1150
Iodine Number, mg/gm	950-1000
CCl <sub>4</sub> Activity, min. (ASTM D-3467)	60
Hardness, min. (ASTM D-3802)	98
Moisture, Max. (ASTM D-2867)	3%
Apparent Density (ASTM D-2854), g/cc lb/ft <sup>3</sup>	0.44-0.46 27-29
U.S. Standard Sieve Size Larger than No. 4, Max. Smaller than No. 6,8, or 10, Max.	4 x 6, 4 x 8, 4 x 10 5% 5%



### STANDARD PACKAGING

55lb or 27.5lb Polylined Polypropylene Bags | 200lb Fiber Drums | 1100lb Supersacks

This information is offered solely for your consideration and verification. It has been gathered from reference materials and/or test procedures and is believed to be true and accurate. None of this information shall constitute a warranty or representation, expressed or implied for which we assume legal responsibility or that the information or goods is fit for any particular use either alone or in combination with other goods or processes.