



# COL-FC60-830

## Liquid Phase, Bituminous Coal Base Carbon

**COL-FC60** is a hard re-agglomerated Granular Activated Carbon (GAC) manufactured from select grades of Bituminous Coal. **COL-FC60** is a high density carbon with a large pore volume and high surface area. Its pore structure has been developed for the adsorption of both high and low molecular weight impurities. **COL-FCL60** is commonly used for purifying potable water, ground water and waste water, and a wide variety of decolorizing/deodorizing applications. **COL-FC60** meets ANSI/NSF Standard 61 and Food Chemicals Codex Standards for drinking water applications.

### TYPICAL PHYSICAL PROPERTIES / SPECIFICATIONS

Iodine Number, min.	900
Apparent Density (ASTM 2854), g/cc	0.50
Abrasion No.	85
U.S. Standard Sieve Size	8x30
<b>Larger than No. 8 max.</b>	15%
<b>Smaller than No. 30 max.</b>	5%
Moisture as packed, max.	2%



### STANDARD PACKAGING

55lb or 27.5lb Polylined Polypropylene Bags | 200lb Fiber Drums | 1100lb Supersacks

This information is offered solely for your consideration and verification. It has been gathered from reference materials and/or test procedures and is believed to be true and accurate. None of this information shall constitute a warranty or representation, expressed or implied for which we assume legal responsibility or that the information or goods is fit for any particular use either alone or in combination with other goods or processes.